



## QUAD FLOW INSTALL GUIDE



**QUAD FLOW CMB**



**QUAD FLOW**

The Quad Flow is designed to sit on the floor and should be installed where the water supply line enters the home. It is best to install so both irrigation and home water are treated by the Quad Flow.

1. The Quad Flow is bi-directional. Water can flow either way through the unit.
2. Designed only for cold water use.
3. There are no filters to change or maintenance for the Quad Flow.
4. The Quad Flow CMB features two refillable ceramic mineral ball water enhancement chambers. These cartridges should be changed yearly and are available from our web store.



Typical installation for the Quad Flow CMB using stainless steel flex connector hoses. The stainless steel multi-round filter housing is installed inline with the Quad Flow.

### **Parts Required**

Stainless steel flex connectors hoses with a shut off valve on the inlet and outlet will work best with the Quad Flow CMB.

When filling the Quad Flow CMB after each filter change, be sure crack valves slightly until the Quad Flow is fully charged with water before opening valves completely.

For the Quad Flow, flex connectors, copper, PEX or PVC may be used to connect to your water supply.

### **Safety**

Check and comply with your state and local building codes. You must follow the guidelines. Use care when handling the structuring system. Any modifications to your current plumbing system should be referred to a qualified plumber.

For assistance with installation or operation, call or email.

Phone: 208-596-6858

Email: [gary@greenfieldnaturals.com](mailto:gary@greenfieldnaturals.com)

### **Product Warranty**

All Greenfield Naturals products are backed by a 90 day, 100% unconditional, money back guarantee if not fully satisfied with product benefits. Additionally, a one-year performance is guaranteed for all products.

